



NOTES:

1. MATERIAL:

- 1.1 HOUSING: LCP COLOR BLACK.
- 1.2 CONTACT: COPPER ALLOY.
- 1.3 PLATING: TIN PLATED OVER NICKEL.

2. ELECTRICAL

- 2.1 CURRENT RATING: 1AMP
- 2.2 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC MIN.
- 2.3 INSULATION RESISTANCE: 500MΩ MIN.
- 2.4 CONTACT RESISTANCE: 30mΩ MAX.

3. ENVIRONMENTAL

- 3.1 TEMPERATURE RANGE: -25°C TO +85°C.
- 3.2 Soldering recommendation: hand soldering

一般公差
GENERAL TOLERANCES

LINEAR		ANGULAR	
.XXX	±0.15	.XX°	±1°
.XX	±0.25	.X°	±2°
.X	±0.35	X°	±3°
X	±---		

核准:
(APPD) **Robert**
审核:
(CHKD) **Pony**
绘图:
(DRAW) **Constant**
日期:
(DATE) 2013 06 06

REV: 1
SCALE: 5:1
SIZE: A4
UNITS:
SHEET:
[Symbol]

料號: SW-2205-M001
(PART. NO)
圖名: SW-2205-M001-001
(TITLE)
圖號:
(DWG. NO)

宏端电子(东莞)有限公司

品名: SW-2205-M001
(MOUD NAME)

修订 REV	修改摘要 REVISION DESCRIPTION	日期 DATE	修改者 DRAW BY